

## MWFA Street Stock Challenge Rules

This class was created to have fun for the fans to watch (Total Carnage). If you come with a vehicle that is built any more than what is listed below you will not run.

1. Any 1980 and newer 2-wheel drive passenger car/ mini-van/ mini-truck/ mid- size suv
2. All vehicles must be stripped off all plastic, glass, headlights, taillights and anything else that could fall off onto the track during the show.
3. All vehicles must remain stock, ABSOULTY NO WELDING ANYWHERE.
4. Bumpers must remain stock, do not alter bumper in anyway. Factory bumper shocks must remain in the factory location. You may remove rear bumper and shocks. There is no welding to be done on bumpers.
5. Batteries may be left in stock location and spray foam may be added around battery. You may also move battery to passenger floor or seat. Please make sure battery is not moving.
6. If factory gas tank is in front of axle you may leave it there. If it's behind the axle you must move it to the rear seat area. Factory tanks may be moved inside but completely secured. After market tanks may be used.
7. All doors may be wired or chained in 6 places max per seam.
8. Trunks, hoods, tailgates, all may be wired or chained in 6 places total. Sheet metal to sheet metal only. Nothing to frame or bumpers. If you remove trunk or tailgate you lose that wire or chain.
9. Cage- You will be allowed a simple 4-point cage. Cage material cannot exceed 6 inch and must be a minimum of 6 inches off all floor tin (this includes trans tunnel). Can only be attached to interior tin only (nothing can go to the floor). Door bars cannot go any further forward or back then the seat bar or dash bar. Rear seat bar must be within six inches of the back side of driver's seat. You will be allowed to have a simple rollover halo that can only be attached to top side of rear seat bar, not to floor. If you choose to run an aftermarket fuel tank you can have a tank mount that is only attached to the rear seat bat only. Size on tank mount cannot exceed 14x14 or just big enough for tank to mount to. Tank mount must be minimum of 6 inches away from all sheet metal
10. DOT tires only. Stock wheels only. All wheel weights must be removed. Only tubes and air are permitted inside of tires.
11. Repair plates- you will be allowed 2-4x4-1/8 max repair plates for either bends or rust, plates must only be on frame rails. If you exceed plate size or abuse this rule, plate will come completely off.

These rules are cut and dry, you should not have to call to ask many questions on this class. If it does not say you can do it then that means YOU CANNOT do it. Quick and easy build.